



# FOUR GAS PERSONAL MONITOR

Gas Detection for Life

GX-2009 Model



## Features

- Simultaneous detection of 4 gases LEL, O<sub>2</sub>, H<sub>2</sub>S & CO
- Smallest / Lightest 4 gas monitor on the market 70 H x 70 W x 25 D mm, 130 g
- Dual audible alarm ports (95 db @ 30 cm)
- 3 visual alarm LED's
- Vibration alarm
- IP-67 Waterproof/dustproof design
- Calibration lock out or reminder controls
- Large capacity data logging standard 8 alarm trends Log time range of 10 to 300 hours 100 calibration records
- 20 hours of operation (NiMH batteries)
- Large LCD display screen
- Automatic backlighting at alarm
- Impact resistant over-mold body, RFI shielded body
- STEL and TWA readouts
- Intrinsically safe, IECEx / ATEX approved (CSA, C/US pending)
- 2 year warranty

## Applications

- Confined Spaces
- Refineries/Petrochemical
- Utilities
- Fire Services
- Hazardous Material
- Personal Monitoring
- Water/Wastewater Plants
- Pharmaceuticals

RKI is proud to offer the smallest and lightest 4-gas monitor in the world, the GX-2009. Weighing only 130g, it fits in the palm of your hand (70 H x 70 W x 25 D mm). The GX-2009 simultaneously monitors and displays combustibles, oxygen, carbon monoxide, and hydrogen sulfide. The GX-2009 represents the latest evolution of gas detection technology. Advancements include dual audible alarm ports and alarm LED's on 3 sides of the instrument, so that alarm conditions are obvious from multiple perspectives especially in high noise environments. Other features include a waterproof and dustproof design with IP 67 rating, an impact resistant rubber over-mold body that is RFI resistant, and a large capacity data logging system included as a standard feature.

Other standard features are vibration alarm, autocalibration, calibration lock out or reminder control, STEL / TWA readings, peak hold, auto backlighting at alarm on a large LCD display, and it even tells the time! All of these controls and features are operated through 2 simple glow-in-the-dark, glove friendly buttons. The NiMH battery set will operate for 20 hours and will fully charge in 3 hours.

A huge capacity data logging function is a standard feature on all GX-2009 instruments, and will store up to 8 alarm trend sessions where readings are recorded 30 minutes before and after an alarm event. The data logging has a 3,600 data point capacity with a log time range of 10 to 300 hours based on programmable interval times. The data logging software will also store up to 100 calibration records and is Windows XP and Vista compatible. The GX-2009 is also functional with the Data Cal 2000 instrument maintenance system and the SM-2009U single calibration station (available in 2009).

The GX-2009 is designed around RKI's compact and proven sensors, utilizing catalytic combustion, electrochemical and galvanic sensor technologies. Each miniaturized sensor is manufactured with the same high quality control that has made RKI sensors and instruments the most reliable and long lasting monitoring devices in the industry.

## Control Equipment Pty Ltd ABN 23 009 838 582

Head Office:  
58 Brookes St  
Bowen Hills QLD 4006

Phone: (07) 3620 5800  
Fax: (07) 3620 5888  
Mobile: 0439 719 172

New South Wales Office:  
Prairiewood NSW 2194

Phone: 1800 174 536  
Fax: (07) 3620 5888  
Mobile: 0418 785 100

Email: [sales@controlequipment.com.au](mailto:sales@controlequipment.com.au) Website: [www.controlequipment.com.au](http://www.controlequipment.com.au)

Authorised Distributors in New South Wales, Victoria, Tasmania, Northern Territory, South Australia and New Zealand

# GX-2009 Model

Gas Detected	All Combustible gases (Methane as standard)	Oxygen (O2)	Hydrogen Sulphide (H2S)	Carbon Monoxide (CO)
<b>Detection Principle</b>	Catalytic Combustion	Galvanic cell	Electro-chemical cell	Electro-chemical cell
<b>Detection Range (Increments)</b>	0 – 100% LEL (1% LEL)	0 – 40.0% Vol (0.1% Vol)	0 – 100 ppm (0.5 ppm)	0 – 500 ppm (1 ppm)
<b>Sampling Method</b>	Diffusion sampling, hand aspirator or motorised pump optional			
<b>Display</b>	Digital LCD displays all four gases simultaneously, with auto backlight			
<b>Present Alarms (User Adjustable)</b>	1st alarm 10% LEL 2nd alarm 50% LEL Over alarm 100% LEL	Low alarm 19.5% High alarm 23.5% Over alarm 40.0%	1st alarm 10 ppm 2nd alarm 30.0 ppm TWA alarm 10 ppm STEL alarm 15 ppm Over alarm 100 ppm	1st alarm 25 ppm 2nd alarm 50 ppm TWA alarm 25 ppm STEL alarm 200 ppm Over alarm 500 ppm
<b>Types of Alarms</b>	Gas Alarm: 2 increasing alarms, STEL, TWA, overscale alarm Trouble Alarm: Sensor disconnection, wire disconnection, low battery, circuit error, calibration range error			
<b>Display of Alarms</b>	Gas Alarm: Flashing LEDs, intermittent buzzer (95dB @ 30cm), flashing gas value, vibration Trouble Alarm: Flashing LEDs, intermittent buzzer (95dB @ 30cm), display of error message			
<b>Operating Temp &amp; Humidity</b>	-20°C to +50°C, 0 to 95% RH, non-condensing (splash resistant)			
<b>Response Time</b>	Within 30 seconds (T90)			
<b>Continuous Operation</b>	20 hours after a full 3 hour charge, (14 hours after a 90 minute charge)			
<b>Power Source</b>	Direct charging NiMH batteries, set of 2			
<b>Safety Design/Approvals</b>	IECEX zone 0 Ex ia IIC T4; ATEX II 1G Ex ia IIC T4; (CSA classified, "C/US", as intrinsically safe. Class I, Division 1, Groups A, B, C, D pending)			
<b>Dimension &amp; Weight</b>	Approx 70 (H) x 75 (W) x 25 (D) mm, approx 130g			
<b>Case Material</b>	RFI shielded high impact over moulded rubber. Dust & waterproof with IP-67 approval			
<b>Controls</b>	Two glow in the dark buttons: POWER/MODE, AIR			
<b>Datalogging</b>	Standard with all instruments. Stores 8 alarm trend events: 3600 data point capacity with a log time range of 10 to 300 hours (based on programmable interval times); and stores up to 100 calibration records.			
<b>Required Accessories</b>	Battery charger			
<b>Standard Accessories</b>	Alligator clip NiMH batteries (set of 2) Charging Station with 115/220 VAC power supply (optional)		R13-0116RK R49-1609RK R49-2170RK	
<b>Optional Accessories</b>	Belt clip Padded carrying case for GX-2009 and accessories Charging station, 115/220 VAC powered for 2, 3, 4 or 5 instruments Charging station with 12 VDC power supply and vehicle adapter plug 12 VDC adapter with vehicle plug (does not include charger base) RP-6 sample drawing pump with 10' hose and probe Hand aspirated sample draw with 10' hose and probe		R13-0117RK R21-0112RK-01 R49-2170RK-XX R49-2171RK R49-2020RK R81-1166RK R81-1160RK	
<b>Configurations</b>	4 gas, LEL / O2 / H2S / CO 2 gas, LEL / O2		3 gas, LEL / O2 / H2S 2 gas, O2 / H2S	
<b>Warranty</b>	Two years material and workmanship			



**Control Equipment Pty Ltd** ABN 23 009 838 582

Head Office:  
58 Brookes St  
Bowen Hills QLD 4006  
AUSTRALIA

Phone: (07) 3620 5800  
Fax: (07) 3620 5888  
Email: sales@controlequipment.com.au  
Website: www.controlequipment.com.au

**Authorised Distributor:**